## ThinkVision T24d

## PROFESSIONAL PERFORMANCE AT WIDE-VIEW DISPLAY.



#### A SI FEK 24" MONITOR WITH OUTSTANDING IMAGE QUALITY.

The sleek, stylish ThinkVision T24d-10 Monitor doesn't just display images - it presents them at over 99% sRGB color gamut and exceptionally crisp 1920 x 1200 resolutions cross near-frameless 24" display. Enjoy vivid images across wide (178°/178°) viewing angles with no color distortion or reflection. With elegant slim design, the monitor fit in any workspace. Get the large visual workspace you need with a professional monitor designed to enhance productivity and make collaboration easy.

#### WHY YOU SHOULD BUY THE THINKVISION T24d-10 MONITOR



#### Performance and **Productivity**

Professional performance defines the WUXGA (1920 x 1200) resolution, over 99% sRGB high color gamut, 1000:1 contrast and In-Plane Switching for exceptional viewing angles across the entire 24" display.



#### **Productivity** at its Finest

A full-function stand ensures your display sports an executive look regardless of whether you swivel, tilt, pivot, or lift. Paired with near-edgeless screen. you can enjoy a clean look and seamless views cross multi-monitor displays.



#### **Ergonomic and** Manageable

The ergonomic full-function stand is perfect for collaboration. It supports the new tiny clamp bracket for easy set-up of the ThinkCentre Tiny. Practical cable management effectively manages desktop clutter.

#### THE THINKVISION T24d-10 MONITOR IS BEST SUITED FOR



Users and businesses that need a highest-quality professional monitor.



Organizations that require highly detailed display for uses like finance or graphics.



Organizations that require professional quality monitors that also deliver a green advantage.

















# ThinkVision T24d-10 MONITOR

#### **SPECIFICATIONS**

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size Panel Type Resolution Backlight Aspect Ratio Pixel Pitch (W x H) (mm) Dot/Pixel Per Inch (DPI/PPI) Anti-Glare Screen Dimensions (W x H) (mm) (inches) Maximum Brightness (Typical) Viewing Angle (H/V at CR 10:1) Contrast Ratio (Typical) Dynamic Contrast Ratio Color Gamut (CIE 1931) Display Colors (Typical) Response Time Extreme Typical Off	24" In-Plane Switching 1920 x 1200 WLED 16:10 0.27 x 0.27 94 PPI Yes  518.4 x 324 20.41" x 12.75" 300 cd/m² 178°/178° 1000:1 3M:1 99% sRGB 16.7 Million  4 ms 7 ms 15 ms	Size Packed (mm) (inches) Size Unpacked with Stand (mm) (inches) Size Monitor Head Only (mm) (inches) Distance from Table to Panel Lowest Pixel at Bottom of Screen (mm / inches) Highest Pixel at Top of Screen (mm / inches) Stand Base Footprint Area (mm) (inches) Weight Packed Unpacked Monitor Head Only	160 x 655 x 422 6.3" x 25.79" x 16.61" 533.2 x 260.4 x 497.4 20.99" x 10.25" x 19.58" 533.2 x 42.3 x 355.1 20.99" x 1.67" x 13.98" 56 / 2.2" 490 / 19.29" 250 x 250 9.84" x 9.84" Starting at 19.18 lbs (8.7 kg) Starting at 12.41 lbs (5.63 kg) Starting at 8.77 lbs (3.98 kg)
SIGNAL INPUT		POWER CONSUMPTION	

#### SIGNAL INPUT

Horizontal Frequency

Video Input Signals
Video Cables Supplied
Video Cable Length
USB Hub
USB Cable Supplied
Video Cable Supplied
Video Cable Length
USB 3.01
USB 3.01
USB 3.01
Ves
Audio-Out
Ves (3.5 mm)

30 kHz - 83 KHz

#### POWER CONSUMPTION

 Typical
 22 W

 Maximum
 64 W

 Sleep-Mode
 <0.3 W</td>

 Switch Off-Mode
 <0.3 W</td>

 Power Supply
 Internal

 Power Voltage
 100 VAC - 240 VAC

 Voltage Dynamic Frequency
 50 Hz - 60 Hz

#### SIGNAL INTERFACE / PERFORMANCE

110112011tai i requericy	30 KHZ - 03 KHZ	
Vertical Frequency	50 Hz - 75 Hz	
Native Resolution	1920 x 1200	
Maximum Pixel Clock Speed/		
Bandwidth		
VGA	205 MHz	
HDMI™	165 MHz	
DisplayPort™	165 MHz	
Default Color Temperature	6500 K	
Preset Display Modes	20	
OSD Buttons	5	
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russiar	

#### ENVIRONMENTAL

Temperature

Operating 0°C - 40°C Non-Operating -20°C - 60°C Humidity Operating 10% - 80% Non-Operating 5% - 95% Altitude Operating 0 m - 5000 m Non-Operating 0 ft - 40,000 ft Arsenic-Free Glass Yes PVC-Free Yes Mercury-Free Yes PCC % of Plastic Resins >85%

#### **MECHANICAL**

Tilt Angle (Front / Back) -5°/ 30° +/-45° Swivel Angle (Left / Right) 110 Lift (mm) +/-90° Pivot 100 x 100 VESA® Mount (mm x mm) Cable Management Yes Kensington® Lock Yes Bezel Color Business Black Bezel Width 2 / 0.08" Top (mm / inches) Bottom (mm / inches) 22.7 / 0.89" Sides (mm / inches) 2 / 0.08"

#### COMPLIANCE

Warranty

Geography Availability

EPEAT Silver
ENERGY STAR Rating 8.0

ULE Gold
TCO TCO Display 7.0 / TCO Edge 2.0

RoHS (EU 2002/95/EC) Yes
China Energy Efficiency Standard Windows Certification Windows 7 / Windows 10

3 Years

ww

WARRANTY AND AVAILABILITY

### \* NA only.

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.2.





#### WWW.LENOVO.COM

# Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for illustration purposes only. For full Lenovo product, service and warranty specifications visit www.lenovo.com. Lenovo makes on representations or warranties regarding third party products or services. Trademarks: The following are trademarks or registered trademarks or Microsoft. Windows and Vista are registered trademarks of Microsoft Corporation. Ultrabook, Celeron, Celeron, Celeron, Celeron, Enisde, Intel, Intel, Logo, Intel Atom Inside, Intel Corp. Intel Inside, Intel Inside Intel Corp. Intel Inside, Inte